



ITONA TC 1330

Thin Client

Networking Ideas

..... Thin Solutions



The new Itona TC1330 desktop is a major breakthrough in the provision of low cost, virtualisation-capable, thin client computing. As VXL's entry level desktop the new model comes at the lowest possible price point, but has features and specification well beyond its price.

Itona TC from VXL is thin client computing perfected. High specifications and low cost add up to a great value package that's secure, easy to manage and highly reliable.



Itona TC 1330

Fully featured

With an extensive range of ports (USB x4, audio, 10/100 Ethernet) Itona has really got connectivity covered. Add to that a 16bit graphics controller capable of 1600x1200 resolution and it all adds up to one of the best specification thin clients around.

The ideal desktop client

The TC1330 has the VMware® View 3.1 client builtin making it "virtualisation ready". Built to VXL's exacting quality specifications, the fan-less design helps make the TC1330 extremely reliable. This, together with the efficient power supply, help record a very low average power usage. All in small, elegant design only 19cm (7.5 inches) high.

Green Credential

With very low average power consumption, the Itona is more than 4 times more efficient than a PC. It is also substantially lower than the majority of its competitors.

Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze

About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide – with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters is in Bangalore, India.

ITONA TC 1330

Thin Client



Modular Terminal

Based on Sylph-OS

Standard Client Software:

ICA Client, PN Agent, RDP, VMWare Client

Hardware

RAM : 256 MB

Flash : 64 MB

Processor : AMD Geode GX466

Input/Output/Peripheral Support :

- 4 USB 2.0 ports (two on front, two on back)
- One VGA-type video output
- Built-in Kensington Security Slot

Networking

- Autosensing, 10/100 Ethernet, RJ-45
- PXE boot

Display Support

- Maximum resolution Supported
16 Bit Color : Upto 1600 x 1200

Audio

- Line Out
- Mic

Physical Characteristics

- Height : 191 mm
- Width : 45 mm
- Depth : 144 mm
- Weight : Approx 0.7 kg.
- Optional : Wall Mounting bracket kit

Environmental

- Temperature Range :
 - Powered on: 5° to 35°C
 - Powered off: -20° to 60°C
 - Convectional cooling, fanless design
- Humidity :
 - 90% maximum, non-condensing

Software

Firmware Features :

- ICA Client : Citrix ICA client for Linux version 10.xx
- VNC Server 4.1.1
- RDP Client : A Remote Desktop Protocol client version 1.6.0
- VMWare View 3.1 Client
- Other : Autostart/auto-restart connections, secure control panel
- Security Features:
 - Read-only file system
- Local Operating System Features
 - Updated kernel version 2.6.x
 - X11R6 local windows manager

Server OS Compatibility/Support :

- Microsoft Windows Terminal Server Edition, Windows 2000 server, Windows 2003 Server, and windows 2008 server
- Citrix MetaFrame

Set-Up and Configuration :

User interface :

- Boot from local Flash
- User Interface Language: U.S. English
- Keyboard language support: US English, UK English, German, Swiss German, French, Swiss French, Italian

Protocol Support :

- TCP/IP, DHCP, FTP, HTTP

Management

- Remote management through XLmanage client management software (included)
- Reboot or Shutdown terminal remotely.
- Complete image and Patch upgrades
- Remote Shadowing

Power

- External power adapter with full range
- Worldwide auto-sensing 100 ~240 VAC at 50Hz ~ 60Hz.
- 2A/12V (24 Watts)

Regulatory Compliance

- Ergonomics : CE
- RF Interference : RoHS, WEEE
- Safety : cULus, TUV-GS, FCC Class B

Warranty

Three-years limited warranty



VXL Instruments Limited

Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India

Tel: +91 80 30222525 (5 lines) Fax: +91 80 28520095 E-mail: sales@vxl.net Web: www.vxl.net

European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD

Tel: +44 (0) 16 17 75 47 55 Fax: +44 (0) 16 17 75 48 66 E-mail: sales@vxl.net



VXL Presence:

France

Tel. : +33 (0) 1 42 17 00 03

E-mail: sales@vxl.net

Germany

Tel. : +49 (0) 8761 1093

E-mail: sales@vxl.net

United States

Tel. : +1 713 589 3273

E-mail: sales@vxl.net